§421.157

PSNS FOR THE PRIMARY BERYLLIUM SUBCATEGORY—Continued

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
Ammonia (as N)	355.245 93.275	156.169 53.034

(m) Beryl Ore Processing.

PSNS FOR THE PRIMARY BERYLLIUM SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of beryl ore processed	
Beryllium	5.988 2.702 9.348 1.461 973.490 255.605	2.702 1.095 4.455 0.584 427.956 145.330

(n) Aluminum Iron Sludge (AIS) Area Wastewater.

PSNS FOR THE PRIMARY BERRYLLIUM SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg (pounds per million pounds) of total beryllium carbonate produced as beryllium	
Dom divers	383.760	170 100
Beryllium		173.160
Chromium (Total)	173.160	70.200
Copper	599.040	285.480
Cyanide (Total)	93.600	37.440
Ammonia (as Ń)	62384.400	27424.800
Fluoride	16380.000	9313.200

(o) Bertrandite Ore Leaching Scrubber.

PSNS FOR THE PRIMARY BERYLLIUM SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average
	mg/kg of bertrandite ore processed	
Beryllium Chromium (Total) Copper Cyanide (Total) Ammonia (as N) Fluoride	1.239 0.559 1.934 0.302 201.416 52.885	0.559 0.227 0.922 0.121 88.545 30.069

40 CFR Ch. I (7-1-12 Edition)

(p) Bertrandite Ore Countercurrent and Decantation (CCD) Scrubber.

PSNS FOR THE PRIMARY BERYLLIUM SUBCATEGORY

Pollutant or pollutant property	Maximum for any 1 day	Maximum for monthly average	
	mg/kg of bertrandite ore processed		
Beryllium	0.083 0.037 0.129 0.020 13.463 3.535	0.037 0.015 0.062 0.008 5.919 2.010	

 $[50~{\rm FR}~38346,~{\rm Sept.}~20,~1985,~{\rm as~amended}~{\rm at}~55~{\rm FR}~31700,~{\rm Aug.}~3,~1990]$

§ 421.157 [Reserved]

Subpart P—Primary and Secondary Germanium and Gallium Subcategory

SOURCE: 50 FR 38350, Sept. 20, 1985, unless otherwise noted.

§ 421.180 Applicability: Description of the primary and secondary germanium and gallium subcategory.

The provisions of this subpart are applicable to discharges resulting from the production of germanium or gallium from primary and secondary germanium and gallium facilities.

§ 421.181 Specialized definitions.

For the purpose of this subpart the general definitions, abbreviations and methods of analysis set forth in 40 CFR part 401 shall apply to this subpart.

§ 421.182 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

Except as provided in 40 CFR 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable technology currently available:

(a) Still liquor.